

Location	Illumination level foot candle (f.c.)
Parking Area	0.6 - 3.6 f.c.
Pedestrian walk- ways and bike ways	0.2 - 2.5 f.c.
Gas Pump Canopy	20 f.c. maximum
Automatic Teller Machines (ATMs)	10 f.c. within 5 feet or 2 f.c. within 50 feet
Dealership (first aisle adjacent to the street)	24 f.c. maximum
Dealership (remaining aisles)	10 f.c maximum

Light levels at the property lines	
When adjacent to commercial	1 f.c. max
When adjacent to residential	0.5 f.c. max



**Downward - reflected lighting** 





# Orange County Exterior Lighting Guidelines

Orange County Code of Ordinances, Chapter 9, Article XVI

#### **Intent and Purpose**

- Exterior lighting shall enhance the visual impact of a building or project.
- Lighting shall be an architectural element.
- Glare, obtrusive light, light trespass, and visual nuisance shall be prohibited.





December 2009

Visit www.orangecountyfl.net/cms/DEPT/growth/planning/urban/ default.htm

## ORANGE COUNTY EXTERIOR LIGHTING STANDARDS AND GUIDELINES





#### **Lighting Fixture**

- Light fixtures shall be incorporated as an integral design element through style, material, and color.
- Lighting fixtures (including wall mounted) shall not be tilted upward.
- Sag lens, convex lens, and drop lenses are prohibited.
- · Floodlights are prohibited.
- Fully horizontal cut-off fixtures are required.

#### **Maximum Mounting Height**

- 30 feet for streets and parking lots.
- 15 feet within non-vehicular pedestrian area.
- 25 feet for 'big box' parking lots.



Mounting height within pedestrian plaza and non-vehicular setting is 15 feet maximum.



### 'Architectural Hold' on building permit, or Certificate of Occupancy?

This will require signed / sealed letter certifying that lighting was installed consistent with Lighting Ordinance.



Mounting height maximum 30 feet for street fixtures

Fixtures with shields

Fixtures without shields